Strong Magnet Antenna Base /Adhesive Backed Mount

Operation Instructions

DIAMOND ANTENNA

To use these products properly, read this instruction thoroughly before using it. Keep this manual carefully at hand for later use.



Waring

To prevent any accident, pay attentions to the following instructions.

①Clean up the installation place. Wipe off moisture, dirt and oil in advance. In case of the dirty surface, the adhesion will be worth. The antenna may be dropped.



②Please make sure if the product is absorbed perfectly every time.

③If hitting branches strongly during driving, the antenna may be dropped or the adsorption surface may be deformed. The vehicle may be damaged.



4) Drive the vehicle at less than 100km/h.

How to maintain

 Iron powder gathered by the magnet causes rust on the vehicle body and damaged. Clean up regularly.
Don't wipe it off with thinner and benzine.
If it is too dirty, wash it with neutral detergent.

Others

- If keeping installing the product under the direct sunlight for a long time, the installation place may be different from the color of the vehicle surface.
- When removing the antenna, cover the connect part with the attached water proof cap.

Installation and Wiring

- ①Be careful not to get rainwater into the vahicle through the coaxial cable.
- When installing and detaching the product, be sure to hold the lower part of the antenna. Pulling the coaxial cable may be caused to damage the vahicle body.

Required Antennas

Please use the antenna (stainless steel) with FOS covered by the following the conditions.

The antenna whose frequency is less than 50MHz cannot be used with these products. SWR will not be lower if installing 1/4 λ antennas (even more than 144MHz) with the product. The radialless antennas are recommended.

Model No.	Length	Weight
K701M (with suction cap)	Less than 1.5m	Less than 350g
K702M (with suction cap)	Less than 1.5m	Less than 350g
K708 Series (with suction cap)	Less than 1.0m	Less than 150g
SPM Series	Less than 1.2m	Less than 350g
DPK Series	Less than 1.2m	Less than 350g
MR2 Series	Less than 1.1m	Less than 250g
MRK (with double-side tape)	Less than 1.0m	Less than 150g
MR5A	Less than 1.0m	Less than 150g

Though these products purchased are manufactured under strict quality control, if a damage is caused by transporting, ask your dealer promptly.

Design and specifications of these products will be changed for future improvement without advance notice.

