



MXseries

Triplexer



	MX-3000	MX-3000N	MX-3000D	MX-3000DM	MX-3300DM	MX-3300MN
Passband width.						
Power rating	LPF:800W(PEP) BPF:500W(PEP) HPF:200W(PEP)				LPF:800W(PEP) BPF:400W(PEP) HPF:200W(PEP)	
Insertion loss (in amateur bands)	LPF:Less than 0.2dB BPF:Less than 0.3dB HPF:Less than 0.4dB				LPF:Less than 0.15dB BPF:Less than 0.25dB HPF:Less than 0.3dB	
Input isolation (in amateur bands)					More than 55dB	
Impedance (in amateur bands)		50 ohms				50 ohms(in amateur band)
VSWR (in amateur bands)			Less than 1.2:1			
Connectors	MIX:N LPF:UHF BPF:UHF HPF:N	MIX:N LPF:UHF BPF:N HPF:N	MIX:N LPF:UHF BPF:UHF HPF:N	MIX:UHF LPF:UHF BPF:UHF HPF:UHF	MIX:UHF LPF:UHF BPF:UHF HPF:N	MIX:UHF LPF:UHF BPF:UHF HPF:N
Coaxial cable	5D-2VS(35cm)			Direct Type		5D-2VS 35cm
Dimensions (W x H x D)						86x25x64mm (3.4"x0.98"x2.5")
Weight	410g(0.90 lbs.)					310g(0.68 lbs)
						385g(0.85 lbs)