



Earphone Microphone / Micro-Auricular

PWR-230X - IP54 Water resistant

PWR-240X - IP54 Water resistant & **Noise cancelling**

Specifications	PWR-230X	PWR-240X
Water-resistant	IP54	
Clip type	Large and strong metal clip allows easy attachment to belts and clothing 360° rotation	
Jack	Patented Twist Lock™ for attaching earpiece to Mic/PTT, 2.5 Earphone jack	
Microphone size (clip included)	35.3x26x26mm	48x24x15mm
Housing	Elegant and strong housing for high impacts.	

Earphone Auricular	PWR-230X	PWR-240X
Diameter	15mm	
Out level	92 dB / 0.05 Watt, 0.01 meter (Artificial Ear IEC-318)	
Input Power	0.1W	
Max Input Power	0.2W	
Output Impedance	32Ω	

Microphone Micrófono	PWR-230X	PWR-240X
Type of element	Non-directional electric condenser	
Sensitivity	-38dB (1V/1Pa)	-47dB (1V/1Pa)
Input Power	2kΩ	2.2kΩ

PWR-230X & PWR-240X are supplied as standard with PWR-EH5 Ear Hook
PWR-230X & PWR-240X se suministran de serie con PWR-EH5 Ear Hook

Optional earphones / Auriculares opcionales:



PWR-EH5



PWR-EH6



PWR-ED7



PWR-EB8



PWR-ET4
(Acoustic tube)



PWR-ET4-E
(Acoustic Ear Hook)
PWR-ET4-OD-E
(Quick-Disconnection Ear Hook)

For other compatible connections, please ask for.
Otras conexiones compatibles, rogamos consultar.



Made with recycled materials



RoHS



MADE IN TAIWAN