


N mount

Overall Size: Ø 41 mm
Mounting Hole: Ø 12.5 mm
Materials: Chromed Brass, Nylon, Rubber
1. N Chrome P/N 2500102.01
2. N Black P/N 2500102.02
3. N 3/8 P/N 2500102.03


NE mount, LOW PROFILE

Overall Size: Ø 36 mm
Mounting Hole: Ø 10 mm
Materials: Chromed Brass, Nylon, Rubber
1. NE Chrome P/N 2500202.01
2. NE Black P/N 2500202.02
3. NE 3/8 P/N 2500202.03


NP mount

Overall Size: Ø 36 mm
Mounting Hole: Ø 12.5 mm
Materials: Chromed Brass, Nylon, Rubber
1. NP Chrome P/N 2500302.01
2. NP Black P/N 2500302.02
3. NP 3/8 P/N 2500302.03


N-PL AS / NE-PL AS mount

Overall Size: Ø 42 mm
Mounting Hole: N-PL Ø 12.5 mm; NE-PL Ø 10 mm
Materials: Chromed Brass, Nylon, Rubber
Connection: UHF-female
1. N-PL AS w/Cap P/N 2500502.05
2. NE-PL AS w/Cap Low profile P/N 2500602.05



Type: Magnetic mount adaptor
Material: Chromed zamac, Nylon
Connection: 1. PL-259-male to DV joint (Black available)
2. PL-259-male to 3/8" thread
1. MAG-DV adaptor P/N 2504502.01
1. MAG-DV adaptor black P/N 2504502.02
2. MAG-3/8 adaptor P/N 2504502.03



Type: Trunk mount
Cable / Connector: 5.5 m RG 58 / UHF-male
Connection: UHF-female, 3/8" Thread or DV joint
1. PL or DV chrome P/N 2504406.12
1. PL or DV black P/N 2504407.13
2. PL or 3/8 Chrome P/N 2504406.14
2. PL or 3/8 Black P/N 2504407.14


MAG H 12 magnetic mount

Frequency Range: from DC to 500 MHz
Overall Size: Ø 92 mm
Materials: Ferrite magnet, Chromed Brass, Nylon, Rubber protection
Cable / Connector: 3.6 m RG 58 / PL 259 R male
MAG H 12 S P/N 2502502.01
MAG H 12 S Black P/N 2502502.02
MAG H 12 3/8 P/N 2502502.03
MAG H 12 PL P/N 2502502.05


MAG 145 magnetic mount

Frequency Range: from DC to 500 MHz
Overall Size: Ø 160 mm
Materials: Ferrite magnet, Chromed Brass, Nylon, Rubber protection
Cable / Connector: 3.6 m RG 58 / PL 259 R male
MAG 145 S P/N 2502702.01
MAG 145 S Black P/N 2502702.02
MAG 145 3/8 P/N 2502702.03
MAG 145 PL P/N 2502702.05

Available Connections


MAG-S
Tiltable Joint chrome or black

MAG-PL
UHF-female connector

MAG-3/8
3/8" connection

MAG 125 magnetic mount

Frequency Range: from DC to 500 MHz
Overall Size: Ø 127 mm
Materials: Ferrite magnet, Chromed Brass, Nylon, Rubber protection
Cable / Connector: 3.6 m RG 58 / PL 259 R male
MAG 125 S P/N 2502602.01
MAG 125 S Black P/N 2502602.02
MAG 125 3/8 P/N 2502602.03
MAG 125 PL P/N 2502602.05


MAG 160 magnetic mount

Frequency Range: from DC to 500 MHz
Overall Size: Ø 166 mm
Materials: Chromed Brass, Nylon, Magnetic rubber
Cable: 3.6 m RG 58 / PL 259 R male
MAG 160 S P/N 2502802.01
MAG 160 S Black P/N 2502802.02
MAG 160 3/8 P/N 2502802.03
MAG 160 PL P/N 2502802.05